

CSPIC-3 is a top class pneumatic grommet attaching machine to accelerate the grommet application process and increase efficiency while securing the consistency of grommet attachment quality. CSPIC-3 carries all superior features of CSPIC-2 and further. Carries an adjustable digital pressure regulator allows the user to set the exact pressure required and keep this pressure consistent for each stroke. Its shaft rotation prevention system allows the user to precisely attach even non-circular accessories. This enhanced machine self greases itself and drains & blows out the humidity in the air coming from the compressor automatically. Laser pointer that allows the operators to locate the grommet's exact position is standard in this machine. With all these superior features, CSPIC-3 is the best choice for whom needs the most precise and consistent pneumatic machine for applying high quantities and variable sizes of grommets with a single machine for years.



- ✔ **Consistent and exact pressure for each stroke.** Regardless of operator expertise and carefulness, CSPIC-3 guarantees you exactly the same application quality in each stroke.
- ✔ **Shaft rotation prevention system.** Precisely attach even non-circular accessories.
- ✔ **Digitally adjustable pneumatic pressure level.**
- ✔ **Moisture control and self drainage.** Drains and blows out the humidity in the air coming from the compressor before reaching the machine. Thus, it avoids rusting problem in the long term.
- ✔ **Hands-free use. CSPIC-3 is operated by a pneumatic foot pedal.** Thus, the operator could use both hands for loading the grommet and adjusting the material during the application.
- ✔ **Advanced Safety System.** Unlike most pneumatic machines' mechanical safety systems that limit the capabilities of the machine, CSPIC-3's safety system senses human static electricity in case the user touches any metal part of the machine and immediately stops the machine. This wise system widely increases the variety of projects that you can handle with CSPIC-3 without risking the operator.
- ✔ **Laser pointer.** A laser pointer is installed on the CSPIC-3 in order to show the operator the exact attaching point.
- ✔ **Self greasing.** No need for external greasing. CSPIC-3 greases itself by its built-in components.
- ✔ **Works with small compressor.**
- ✔ **Completely assembled.** Comes as shown in the picture, with a built in table.

CSPIC-3

Technical Data

Throat Depth (from the center of the die)	85 mm	3 1/4 inches
Applicable Grommet Sizes	#12 (40 mm hole size) and smaller sizes	
Net Weight	53 kg	117 lbs.
Dimensions (Height*Width*Depth)	1230x540x540 mm	48 1/2 x 21 1/4 x 21 1/4 inches

